



## SPECIAL CHARACTERISTICS

- Lightweight
- Extremely compact
- Economical
- Low maintenance
- Easily installed
- Tight shut-off
- One moving part
- Retained disc

Model	526	546
Body	Steel	316 S.S.
Fixings	316 S.S.	316 S.S.
Disc	316 S.S.	316 S.S.
Seat	E.P.D.M.	Suffix 'E'

## Principle Dimensions

Nominal size 'DN' (mm)	40	50	65	80	100	125	150	200	250	300
Inlet bore 'DI' (mm)	26	35	46	57	80	102	125	166	208	250
Min. out. pipe bore (mm)	40	50	65	78	100	125	150	200	250	300
Length 'L' (mm)	16	16	16	16	16	16	19	29	29	38
Outside diameter 'DO' (mm)	See table on page 3									
Weight (Kg)	1	2	2	3	4	5	6	14	25	48

Working temperatures up to 100°C

Working pressures up to 20 Bar

### Abacus Wafer Check Valves

t: +44 (0)1505 681777

f: +44 (0)1505 683999

www.abacusvalves.com  
sales@abacusvalves.com

Block 4 Lochshore East  
Industrial Estate Glengarnoch  
Ayrshire KA14 3DB

## NOTES

- Wafer pattern design offers significant space and weight reduction compared with traditional flanged valve design
- Superior by design
- 24 hour quotation turn around
- Comprehensive stocks
- Worldwide distribution
- Technical assistance and advice always available